

**Features:**

- Ideal for Field Uniformity to EN61000-4-3
- Low Dielectric Materials
- Adjustable Height From 25 cm to 240 cm
- Graduated Scale in 1 mm Increments
- Stable, Sturdy Platform
- Floor View Finder for Convenient Probe Location in Chamber
- Compatible with all ETS-Lindgren EMC Probes
- Offsets Provided for ETS-Lindgren EMC Probes for Sensor Centers
- 1/4" 20 UNC Probe Mount
- Easily Disassembled for Storage



ETS-Lindgren's Model H-491269 Probe Stand

The Model H-491269 Probe Stand is designed for accurate and repeatable probe positioning when performing field uniformity calibrations in accordance with 61000-4-3 and 61000-4-21, among other EMC and military standards. Additionally, this probe stand can be utilized for any precision positioning requirement.

**Physical Specifications**

MODEL	BASE AND TUBE HEIGHT	BASE PLATE	PROBE MOUNTING SURFACE MINIMUM	PROBE MOUNTING SURFACE MAXIMUM	TUBE WIDTH	LOAD CAPACITY PER CARRIER
H-491269	243.8 cm 96.0 in	40.6 cm 16.0 in	25.0 cm 9.8 in	240.0 cm 94.5 in	224.8 cm 88.5 in	600 g 21 oz.

**USA:**

Tel +1.512.531.6400  
Fax +1.512.531.6500

**FINLAND:**

Tel +358.2.8383.300  
Fax +358.2.8651.233

**UK:**

Tel +44.(0)1438.730700  
Fax +44.(0)1438.730751

**FRANCE:**

Tel +33.1.48.65.34.03  
Fax +33.1.48.65.43.69

**CHINA:**

Tel +8610.8275.5086  
Fax +8610.8275.5537

**JAPAN:**

Tel +81.3.3813.7100  
Fax +81.3.3813.8068

**ONLINE:**

info@ets-lindgren.com  
www.ets-lindgren.com